

## PRODUCT **SPECIFICATIONS**

#### Frame/Fork

Frame	6061 Aluminum Frame, Rear 160mm Post Mount Brake Tab		
Fork	Cro-Mo Steel Fork, Tapered Steerer 1-1/2" to 1-1/8", 386mm Axle-to-Crown Length, 42mm Rake, Post Mount 160mm Disc Tab		

#### **Cockpit Components**

Handle Bar	710mm Wide, 31.8mm Clamp , 125mm Rise, 15* Back Sweep		
Grips	Radio Flyer Rubber/Aluminum Clamp On		
Stem 90mm Length, 45* Fixed Angle, 31.8mm clamp			
Seat Post31.6mm Diameter, 350mm length, 20mm offsetSaddleSelle Royal Freeway Gel -186mm Width			
		Headset	44mm - Zero Stack, Tapered 1-1/2" to 1-1/8" - Sealed Bearing

#### Brakes

Lever	TektroHD-E350 Hydraulic Lever with power cut-off sensor
Caliper	Tektro HD-e350 Hydraulic Caliper with Green Organic Pads
Rotor	Tektro 180mm

#### Wheels

Rims	Alloy Double Wall (36H Front) (36H Rear)		
Hub	Front -15mm Thru Axle, / Rear 12mm Axle 18mm Nut, Sealed Bearing, HubMotor		
Tire	Front 24" x 2.4" - Rear 20" x 2.4" - Kenda Puncture Resistant		


#### **Drive Train**

Motor System	500W brushless Hub Motor		
Battery Pack	48V 15Ah (687Wh) UL Tested Lithium-Ion Samsung 50E 21700 Cells		
Shift lever	Shimano SL-TX50-7R shifter		
Rear Derailleur	Shimano TY300 7-speed derailleur		
Crank Arm	165mm Forged Alloy		
Chain Ring	56T / Single Sided Chainguard		
Cassette	14-28 Shimano Freewheel		
Chain	KMC Z7 Speed		
Pedal	Welgo Plastic Platform - Integrated reflectors, CR-Moly axle, 9/16" x 20 TPI threads		

#### **Extras**

Head Light	LED
Taillight	LED with integrated Brake Light and Turn Signal Functions
Fender	Front Fender and Rear Fender with Side Covers Included
Kickstand	Rigid, 2 Leg Center Stand

#### **Bike Geometry**



Trail

0

Bike Total Length Bike Width (Handle Bike Height Rear Rack Height Rear Rack Length Rear Rack Cargo Ca Front Cargo Capaci Max Gross Vehicle Bike Weight withou Bike Weight with A

### **Rider Fit**

	Saddle Height fror (Top of hip should
	Standover Height (Should be able to
	Handlebar Height
	Max Rider Weight
	Recommended Mi
	Recommended Ma

# FLYER.

BY RADIO FLYER

	SMALL	MEDIUM	LARGE
9	1298mm	1332mm	1368mm
er	605mm	640mm	675mm
r/Chain Stay Length	694mm	694mm	694mm
acket Height	285mm	285mm	285mm
acket Drop It Wheel)	40mm	40mm	40mm
_ength	380mm	450mm	505mm
Angle	73*	73*	73*
Length	180mm	205mm	220mm
Angle	71*	71*	71*
k	559mm	577mm	630mm
ch	379mm	407mm	454mm
op Tube Length	550mm	583mm	646mm
h - Axle To Crown	386mm	386mm	386mm
Offset	42mm	42mm	42mm
	62mm	62mm	62mm

#### **Bike Overall Dimensions**

SMALL	MEDIUM	LARGE
75	75	77
29.5"	29.5″	29.5″
41.5″	43"	45″
25.5″	25.5″	25.5″
28.5″	28.5″	28.5″
150lbs	150lbs	150lbs
25lbs	25lbs	25lbs
400lbs	400lbs	400lbs
69lbs	70lbs	70lbs
80lbs	81lbs	81lbs
	75 29.5" 41.5" 25.5" 28.5" 150lbs 25lbs 400lbs 69lbs	75 75   29.5" 29.5"   41.5" 43"   25.5" 25.5"   28.5" 28.5"   150lbs 150lbs   25lbs 25lbs   400lbs 400lbs   69lbs 70lbs

	SMALL	MEDIUM	LARGE
m Ground I be in range)	28.5" - 37"	32" - 40.5"	34.5-43"
o step over)	18″	18.5″	19″
from Ground	40.5" - 41.5"	42-43"	44-45"
	220lbs	220lbs	220lbs
inimum Rider Height	4' 10"	5′3″	5'10"
aximum Rider Height	5′10″	6'3"	6′10″